PS-350 C

Compact class chain saw

.





Large, easy accessible tank caps



The externally mounted sprocket makes fitting the chain simple and uncomplicated



Die-cast magnesium engine block for strong torque production



Touch&Stop one lever operating

Technical specifications			
Displacement	34,7 cm³	Automatic oilpump	yes
Power rating	1,5 kW	Catalytic converter	yes
Power rating	2,0 PS	Sound pressure level	100,8 dB(A)
Net weight	4,8 kg	Sound power level	110,0 dB(A)
Fuel tank capacity	0,48 l	Power factor K	2,5 dB(A)
Oil tank capacity	0,28 l	Vibration acceleration Front	4,3 m/s²
Vibration damping	yes	Vibration acceleration Rear	3,6 m/s²
Chain tensioning	Lateral tensioning	Power factor K	2,0 m/s²

- Easy Start: Spring assisted starter combined with optimized engine management
- SafetyMatic chain brake
- Centrifugal clutch with 3 weights
- Outside sprocket
- Adjustable oil pump, disabled at engine idling
- Touch&Stop one lever service
- Magnesium diecasting housing
- Catalytic converter to clean the exhaust gases
- Toolless airfilter maintenance
- Summer / winter operation
- Lateral chain tensioning
- Big tank cap, S-form for easy operation

DOLMAR GmbH - A member of the Makita group . Jenfelder Str. 38 . 22045 Hamburg
www.dolmar.com